

# AIP SUPPLEMENT - SUOMI / FINLAND

Aeronautical Information Service

www.ais.fi

Fintraffic ANS, PL 157, FI-01531 VANTAA, ais@fintraffic.fi

AIP SUP NR  
**078 / 2026**

**AIRAC**

**WEF**  
**11 JUN 2026**

## TAMPERE-PIRKKALAN LENTOASEMA (EFTP), TILAPÄINEN KIIOTIE 06C/24 AJALLA 11.6. - 6.8.2026

REF AIP SUP 077/2026

1. Kiiotie 06C/24 on perustettu ajalle **11.6. - 6.8.2026** lentoasemalla tehtävien rakennustöiden vuoksi alla esitettyjen tietojen mukaisesti. Ks. myös sivulla 3 oleva kuva.

Käytettävä kiiotie (06C/24 tai 06/24) tullaan kertomaan NOTAMilla.

## TAMPERE-PIRKKALA AERODROME (EFTP), TEMPORARY RUNWAY 06C/24 FROM 11 JUN to 06 AUG 2026

REF AIP SUP 077/2026

1. Runway 06C/24 is established due to construction work **from 11 JUN to 06 AUG 2026** according to the data given below. See also the sketch on page 3.

The runway in use (06C/24 or 06/24) will be published by NOTAM.

### AIP, EFTP AD 2.12 KIIOTIEN OMINAISTIEDOT RUNWAY PHYSICAL CHARACTERISTICS

RWY ID	TRUE BRG	DMN RWY M	PCN and SFC of RWY and SWY	THR COORD RWY end COORD THR GUND	THR ELEV TDZ ELEV
1	2	3	4	5	6
06C	064.44	2277 x 45	PCN 75/F/A/W/T ASPH SWY: NIL	612438.02N 0233519.43E 612509.73N 0233737.95E GUND: 61.6 FT	THR: 388.5 FT TDZ: 387.7 FT
24	244.48	2277 x 45	PCN 75/F/A/W/T ASPH SWY: NIL	612509.73N 0233737.95E 612438.02N 0233519.43E GUND: 61.6 FT	THR: 367.5 FT TDZ: 375.6 FT

RWY ID	RWY / SWY Slope	SWY DMN M	CWY DMN M	STRIP DMN M	RESA DMN M	RAG	OFZ
1	7	8	9	10	11	12	13
06C	REF AIP SUP 079/2026	NIL	NIL	2397 x 300	240 x 90	Arresting cable 300 M FM THR NET	NIL
24	REF AIP SUP 079/2026	NIL	NIL	2397 x 300	TEMPO 240 x 90	NIL	NIL

RWY ID	RMK
1	14
24	Turn pad LEN 141 M, WID MAX 82 M  Kääntymislevennys poikkeaa ICAO Doc 9157, Aerodrome Design Manual, Part 1, Runways, ohjeistuksesta. Turn pad deviates from guidance of ICAO Doc 9157, Aerodrome Design Manual, Part 1, Runways. REF EFTP AD 2.4 - 1.

**AIP, EFTP AD 2.13 LYHENNETYT LASKENNALLISET PITUUDET  
REDUCED DECLARED DISTANCES**

<i>RWY ID RWY INT</i>	<i>TORA M</i>	<i>TODA M</i>	<i>ASDA M</i>	<i>LDA M</i>	<i>RMK</i>
1	2	3	4	5	6
<del>06 (B)</del>	2515	2515	2515	<del>NIL</del>	<del>NIL</del>
06C (C)	2117	2117	2117	NIL	NIL
06C (J)	1815	1815	1815	NIL	NIL
06C (K)	1186	1186	1186	NIL	NIL
24 (D)	1614	1614	1614	NIL	NIL
24 (G)	1928	1928	1928	NIL	NIL
24 (H)	1560	1560	1560	NIL	NIL
24 (K)	1113	1113	1113	NIL	NIL

**AIP, EFTP AD 2.14 LÄHESTYMIS- JA KIITOTIEVALOT  
APPROACH AND RUNWAY LIGHTING**

<i>RWY ID</i>	<i>APCH LGT type LEN INTST</i>	<i>THR LGT colour WBAR</i>	<i>VASIS (MEHT) PAPI</i>	<i>TDZ LGT LEN</i>	<i>RCL LGT LEN spacing colour INTST</i>	<i>REDL LEN spacing colour INTST</i>	<i>RENL colour WBAR</i>	<i>SWY LGT LEN colour</i>	<i>RMK</i>
1	2	3	4	5	6	7	8	9	10
06C	NIL	G LIH FLG W LIH	PAPI Left side/3° (48 FT)	NIL	NIL	W LIH YCZ 600 M	R LIH	NIL	APCH W LIH, APCH R LIL: LED
24	CAT I 900 M W LIH R LIL	G LIH WBAR	PAPI Left side/3° (54 FT)	NIL	NIL	W LIH YCZ 600 M	R LIH	NIL	NIL

**AIP, EFTP AD 2.25 VSS LÄPÄISYT  
VISUAL SEGMENT SURFACE (VSS) PENETRATIONS**

NR	COORD	ELEV FT	Penetration FT	IAP
1.	612436.0N 0233439.1E	456	12.5	EFTP RNP RWY 06C
2.	612435.8N 0233439.9E	443	0.2	

**2. Merkinnät**

**THR RWY 06C** on merkitty tilapäisen siirretyn kynnyksen merkinnöillä (kiitotien yli maalattu valkoinen viiva ja nuolet).

**2. Markings**

**THR RWY 06C** is marked by temporary DTHR markings (a white stripe across the runway and arrows).

**TAMPERE-PIRKKALA AD (EFTP) - RWY 06C/24  
11 JUN - 06 AUG 2026**

