

AIP SUPPLEMENT - SUOMI / FINLAND

Aeronautical Information Service

www.ais.fi

Fintraffic ANS, PL 157, FI-01531 VANTAA, ais@fintraffic.fi

AIP SUP NR
104 / 2026

AIRAC

WEF
09 JUL 2026

TAMPERE-PIRKKALAN LENTOASEMA (EFTP), TILAPÄINEN KIIOTIE 06/24C AJALLA 9.7. - 3.9.2026

REF AIP SUP 103/2026

1. Kiiotie 06/24C on perustettu ajalle **9.7. - 3.9.2026** lentoasemalla tehtävien rakennustöiden vuoksi alla esitettyjen tietojen mukaisesti. Ks. myös sivulla 3 oleva kuva.

Käytettävä kiiotie (06/24C tai 06/24) tullaan kertomaan NOTAMilla.

TAMPERE-PIRKKALA AERODROME (EFTP), TEMPORARY RUNWAY 06/24C FROM 09 JUL to 03 SEP 2026

REF AIP SUP 103/2026

1. Runway 06/24C is established due to construction work **from 09 JUL to 03 SEP 2026** according to the data given below. See also the sketch on page 3.

The runway in use (06/24C or 06/24) will be published by NOTAM.

AIP, EFTP AD 2.12 KIIOTIEN OMINAISTIEDOT RUNWAY PHYSICAL CHARACTERISTICS

RWY ID	TRUE BRG	DMN RWY M	PCN and SFC of RWY and SWY	THR COORD RWY end COORD THR GUND	THR ELEV TDZ ELEV
1	2	3	4	5	6
06	064.44	2399 x 45	PCN 75/F/A/W/T ASPH SWY: NIL	612438.02N 0233519.43E 612505.55N 0233719.65E GUND: 61.6 FT	THR: 391.4 FT TDZ: 390.3 FT
24C	244.48	2399 x 45	PCN 75/F/A/W/T ASPH SWY: NIL	612505.55N 0233719.65E 612438.02N 0233519.43E GUND: 61.6 FT	THR: 368.6 FT TDZ: 375.7 FT

RWY ID	RWY / SWY Slope	SWY DMN M	CWY DMN M	STRIP DMN M	RESA DMN M	RAG	OFZ
1	7	8	9	10	11	12	13
06	REF AIP SUP 105/2026	NIL	NIL	2519 x 300	TEMPO 240 x 90	Arresting cable 723 M FM THR	NIL
24C	REF AIP SUP 105/2026	NIL	NIL	2519 x 300	240 x 90	NET	NIL

RWY ID	RMK
1	14
06	Turn pad LEN 141 M, WID MAX 82 M Kääntymislevennys poikkeaa ICAO Doc 9157, Aerodrome Design Manual, Part 1, Runways, ohjeistuksesta. Turn pad deviates from guidance of ICAO Doc 9157, Aerodrome Design Manual, Part 1, Runways. REF EFTP AD 2.4 - 1.

**AIP, EFTP AD 2.13 LASKENNALLISET PITUUDET
DECLARED DISTANCES**

<i>RWY ID</i>	<i>TORA M</i>	<i>TODA M</i>	<i>ASDA M</i>	<i>LDA M</i>	<i>RMK</i>
1	2	3	4	5	6
06	2399	2399	2399	2399	NIL
24C	2399	2399	2399	2399	NIL

**LYHENNETYT LASKENNALLISET PITUUDET
REDUCED DECLARED DISTANCES**

<i>RWY ID RWY INT</i>	<i>TORA M</i>	<i>TODA M</i>	<i>ASDA M</i>	<i>LDA M</i>	<i>RMK</i>
1	2	3	4	5	6
06 (B)	2215	2215	2215	NIL	NIL
06 (C)	1816	1816	1816	NIL	NIL
06 (J)	1514	1514	1514	NIL	NIL
06 (K)	886	886	886	NIL	NIL
24C (D)	2036	2036	2036	NIL	NIL
24C (G)	2351	2351	2351	NIL	NIL
24C (H)	1983	1983	1983	NIL	NIL
24C (K)	1536	1536	1536	NIL	NIL

**AIP, EFTP AD 2.14 LÄHESTYMIS- JA KIITOTIEVALOT
APPROACH AND RUNWAY LIGHTING**

RWY ID	APCH LGT type LEN INTST	THR LGT colour WBAR	VASIS (MEHT) PAPI	TDZ LGT LEN	RCL LGT LEN spacing colour INTST	REDL LEN spacing colour INTST	RENL colour WBAR	SWY LGT LEN colour	RMK
1	2	3	4	5	6	7	8	9	10
06	CAT I 900 M W LIH R LIL	G LIH WBAR	PAPI Left side/3° (55 FT)	NIL	NIL	W LIH YCZ 600 M	R LIH	NIL	APCH W LIH, APCH R LIL: LED
24C	NIL	G LIH FLG W LIH	PAPI Left side/3° (48 FT)	NIL	NIL	W LIH YCZ 600 M	R LIH	NIL	NIL

2. Merkinnät

THR RWY 24C on merkitty tilapäisen siirretyn kynnyksen merkinnöillä (kiitotien yli maalattu valkoinen viiva ja nuolet).

2. Markings

THR RWY 24C is marked by temporary DTHR markings (a white stripe across the runway and arrows).

**TAMPERE-PIRKKALA AD (EFTP) - RWY 06/24C
09 JUL - 03 SEP 2026**

